



PA Specifications

| | AR96 | i | AR120 | |
|----------------------------------|---------------|-----------------------------------------------------------|------------|--|
| Working Width | 86" | | 116" | |
| Overall Width | 97.375 | 5" | 127.625" | |
| Overall Length | 136" in | 136" in transportation position | | |
| Overall Height (with tines on th | e ground) | 44.25 | | |
| Weight (w/o added weight) | 1,700 H | os. | 2,200 lbs. | |
| Number of Tines | 24 LH & 2 | 4 RH 32 | LH & 32 RH | |
| Tine Material | Forge | Forged & Heat Treated Steel | | |
| Tine Hub Spacing | | 7.5" | | |
| Tine Penetration | Up to 8.125" | Up to 8.125" depending on ground condition | | |
| Frame Construction | 4" Sq. tubi | 4" Sq. tubing all welded construction | | |
| Hitch Type | Heavy duty | Heavy duty pull type with clevis hitch 1.25" max pin dia. | | |
| | 1 | | | |
| Main Tongue Beam | | 4" Sq. | | |
| Hitch Jack | 10" top w | 10" top wind jack mounted to frame | | |
| Rotor/Tine Support Hangers | 1" x 7 | 1" x 7" heavy duty hangers | | |
| Rotor Bearings | Heavy o | Heavy duty greaseable bearings | | |
| Rotor Bearing Protection | .375' | .375" x 3.5" metal housing | | |
| Rotor Angle Adjustment | | 2.5°, 5°, 7.5° | | |
| Tires & Wheels | 9.5l x 15 8 l | 9.51 x 15 8 PLY RIB TL ROLLED RIM 5 ON 5.5 BHC | | |
| | | | | |
| Tine Depth Control | Add cylinder | Add cylinder donuts to cylinder rod- included | | |
| Hydraulic Cylinder | 3.5 | 3.5" x 8" ASAE toe rod | | |
| Transportation Lock | M | Manual cylinder lock | | |
| Rear Axle Pivot | | Greaseable | | |

Dirt Dog's PA Series pull-type Pasture Aerators are ideal in agricultural conservation tillage and pasture renovations. The heavy-duty, knife-like tines on the aerator are designed with a twist in them to break-up compacted soil horizontally and vertically as they slice into the ground in a twisting fashion. This breaking action conditions the soil to soak up run-off water faster, allow fertilizer to penetrate deeper into the ground, and increase oxygen and water supplies to the plant roots. Optional concrete weights help aerator tines penetrate the ground at their maximum depth.

- ·□4" x 4" x 5/16" frame construction
- · Hydraulically adjustable transport wheels standard
- ·□ All metal weight box available
- ·□Heavy duty grease able bearings
- •□ Rotors can be adjusted from 2 1/2, 5 and 7 1/2 degrees.
- ·□Tines spaced 7 1/2" apart
- Times are designed with a twist to lift while fracturing the soil sideways
- · Available in Yellow, Red, Orange, Green and Blue

www.DIRTDOGMFG.com

2405 US 441 South - Commerce, GA 30529 - 706.335.4647