



DIRT DOG

PASTURE AERATOR



Take a Picture of This QR Code With Your Smart Phone to See it in Action



FEATURES & BENEFITS

- 4" x 4" x 5/16" frame construction
- Hydraulically adjustable transport wheels standard
- All metal weight box available
- Heavy duty greaseable bearings
- Rotors can be adjusted from 2 1/2, 5 and 7 1/2 degrees
- Tines spaced 7 1/2" apart

SPECIFICATIONS / OPTIONS

Models	PA8	PA10
Horse Power	40-90	40-90
Working Width	86"	116"
Overall Width	97 3/8"	127 5/8"
Overall Length (Wheels Down)	136"	136"
Overall Height (with tines on the ground)	44 1/4"	44 1/4"
Weight (w/out added weight)	1950 lbs.	2500 lbs.
Max Ballast in Weight Box	2200 lbs.	2900 lbs.
Number of Tines	24 LH & 24 RH	32 LH & 32 RH
Tine Material	Forged & heat treated steel	Forged & heat treated steel
Tine Hub Spacing	7 1/2"	7 1/2"
Tine Penetration	Up to 8.125" depending on ground condition	Up to 8.125" depending on ground condition
Frame Construction	4" Sq. tubing all welded construction	4" Sq. tubing all welded construction
Hitch Type	Heavy duty pull type with clevis hitch 1.25" max pin dia.	Heavy duty pull type with clevis hitch 1.25" max pin dia.
Main Tonque Beam	4" Sq.	4" Sq.
Hitch Jack	10" top wind jack mounted to frame	10" top wind jack mounted to frame
Rotor/Tine Support Hangers	1" x 7" heavy duty hangers	1" x 7" heavy duty hangers
Rotor Bearings	Heavy duty greaseable bearings	Heavy duty greaseable bearings
Rotor Bearing Protection	3/8" x 3 1/2" metal housing	3/8" x 3 1/2" metal housing
Rotor Angle Adjustment	2.5°, 5°, 7.5°	2.5°, 5°, 7.5°
Tires & Wheels	9 5L x 15 8 PLY RIB TL ROLLED RIM 5 ON 5.5 BHC	9 5L x 15 8 PLY RIB TL ROLLED RIM 5 ON 5.5 BHC
Tine Depth Control - DO NOT TURN W/TINES IN GROUND	Add cylinder donuts to cylinder rod- included	Add cylinder donuts to cylinder rod- included
Hydraulic Cylinder	3 1/2" x 8" ASAE tie rod	3 1/2" x 8" ASAE tie rod
Transportation Lock	Manual cylinder lock	Manual cylinder lock
Rear Axle Pivot	Greaseable	Greaseable

Available Colors:

