



DIRT DOG®

RT200 Series Rotary Tiller Gear Drive



**Available in
5', 6' & 7' widths**

Ground breaking news from Dirt Dog... the new RT Series gear driven tillers, designed and built in Commerce, Georgia, can handle your toughest tilling needs. From establishing a garden to planting a wildlife food plot to incorporating soil amendments for nutrient enhancement, the RT Series tillers from Dirt Dog are built tough to help you get the job done fast. Available in 5-foot, 6-foot and 7-foot tilling widths in both forward and reverse tine rotations, the all-welded steel frame construction houses a side drive gearbox that transfers power to the rotor where 6-blades per flange deliver optimized soil tilling. An adjustable swinging tailgate smooths the tilled soiled leaving a clean finish ready for planting. The RT units are equipped with an innovative, spring-loaded parking stand that makes hitching and unhitching the units a breeze. When you desire optimum tilling performance in a solidly built machine at an affordable price, look no further than the RT Series tiller line from Dirt Dog! Contact your local Dirt Dog dealer to find out more on this exciting series of tillers.

706-335-4647

DirtDogmfg.com



Gear Drive Rotary Tiller

Cat 1 Standard and Quick Hitch with dual hitch lug mounting

The RT Series is developed to fit both standard and quick hitch mounting arrangements. The RT205 and RT206 models fit Category 1 standard and quick hitch while the RT207 accommodates both Category 1 and 2 standard and quick hitch arrangements. All units are designed with full width A-frame mast halves that give incredible strength to the hitch area, along with dual, or straddle mounted, lower lift lugs that allow for a strong, even pull.

Adjustable skid shoes

Easily adjustable skid shoes allow the operator to set the digging depth according to his needs up to a maximum digging depth of 7-1/2 inches (can require multiple passes based on ground conditions)

Retractable parking stand and Hideaway driveline holder

When the work is done and the RT tiller is stored, the innovative, spring-loaded parking stand makes securely parking the unit a snap while the driveline holder folds down into place and keeps the driveline out of the dirt.



Floating tailgate

The floating tailgate feathers out the tilled soil leaving it seedbed ready.



Gear driven

The rugged side gear drive powers the RT tillers through the toughest ground conditions at just the right rotor speed. The side gear drive is bathed in oil for long life and is covered by a stamped housing that provides strength and rigidity with an aesthetic look.

Gearbox warranty

Limited 5-year gearbox warranty covering both the input gearbox and the side drive gearbox; standard 1-year warranty on the balance of the machine (see op manual for complete details)

Models

	RT205/R	RT206/R	RT207/R
Rotation	Forward/Reverse		
Drivetrain	Gear	Gear	Gear
Hitch	Cat 1 + QH	Cat 1 + QH	Cat1 & 2 + QH
Working Width	59"	70 1/2"	82 1/2"
Overall Width	66"	78"	90"
# of Flanges	7	9	11
Blades per Flange	6	6	6
Rotor/Blade Rotation Diameter	17"	17"	17"
Rotor Shaft Diameter	3"	3"	3"
Rotor RPM	211	211	211
Weight	697 lbs.	770 lbs.	845 lbs.
PTO Driveline with Slip clutch	ASAE Cat 4	ASAE Cat 4	ASAE Cat 5
Tilling Depth (Multiple Passes)	7 1/2"	7 1/2"	7 1/2"
Min/Max Tractor H.P. (PTO)	25 / 45	35 / 55	45 / 65
Powder Coated Colors	Red, Green, Orange, Blue & Yellow		

Made in Commerce, GA



Available Nationwide

www.DirtDogmfg.com