



9" CULTIPACTOR



Take a Picture of This QR Code With
Your Smart Phone to See It in Action



FEATURES & BENEFITS

- Greasable bearings
- Optional scraper kits available
- Available with 9.64" notched wheels, 15" smooth wheels or 16.3" notched wheels
- Min. HP recommended - 35 hp
- Parking stand is standard
- CP - 3 Point cultipacker features

SPECIFICATIONS / OPTIONS

Models	CP960	CP972	CP984	CP996
Product Description	3PT Cultipacker 60" / 9.64" wheel	3PT Cultipacker 72" / 9.64" wheel	3PT Cultipacker 84" / 9.64" wheel	3PT Cultipacker 96" / 9.64" wheel
Height	33.11"	33.11"	33.11"	33.11"
Width	67.19"	80.38"	91.78"	103.19"
Working Width	59.28"	72.98"	84.36"	95.76"
Depth	16.79"	16.79"	16.79"	16.79"
Weight	427 lbs.	501 lbs.	564 lbs.	625 lbs.
Number of Wheels	26	32	37	42
Wheel Width	2.28"	2.28"	2.28"	2.28"
Wheel Diameter	9.64"	9.64"	9.64"	9.64"
Wheel Material	Notched Gray Iron	Notched Gray Iron	Notched Gray Iron	Notched Gray Iron
Axel	1 3/4"	1 3/4"	1 3/4"	1 3/4"
Bearings	Greasable	Greasable	Greasable	Greasable
Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch

Available Colors:





15" CULTIPACTOR



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



FEATURES & BENEFITS

- 15" smooth gray iron wheels
- 2" axle
- Category 1 Quick Hitch compatible
- Scraper kit available
- Min. HP recommended is 35 HP
- Parking stand is standard

SPECIFICATIONS / OPTIONS

Models	CP1560	CP1572	CP1584	CP1596
Product Description	Cultipacker 60" / 15" wheel	Cultipacker 72" / 15" wheel	Cultipacker 84" / 15" wheel	Cultipacker 96" / 15" wheel
Height	37.53"	37.53"	37.53"	37.53"
Width	67.72"	80.91"	92.31"	103.72"
Working Width	59.96"	71.96"	83.96"	95.96"
Depth	20.47"	20.47"	20.47"	20.47"
Weight	712 lbs.	835 lbs.	954 lbs.	1073 lbs.
Number of Wheels	15	18	21	24
Wheel Width	4"	4"	4"	4"
Wheel Diameter	15"	15"	15"	15"
Wheel Material	Smooth Gray Iron	Smooth Gray Iron	Smooth Gray Iron	Smooth Gray Iron
Axel	2"	2"	2"	2"
Bearings	Greasable	Greasable	Greasable	Greasable
Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch

Available Colors:





16" CULTIPACTOR



Take a Picture of This QR Code With
Your Smart Phone to See It in Action



TRACTOR

FEATURES & BENEFITS

- Scraper Kit available
- Min. HP recommended 35hp
- Parking stand is standard
- 2" axle
- Category 1 Quick Hitch compatible
- Greasable bearings

SPECIFICATIONS / OPTIONS

Models	CP1660	CP1672	CP1684	CP1696
Product Description	Cultipacker 60" / 15" wheel	Cultipacker 72" / 15" wheel	Cultipacker 84" / 15" wheel	Cultipacker 96" / 15" wheel
Height	33.18"	33.18"	33.18"	33.18"
Width	67.72"	80.91"	92.31"	103.72"
Working Width	60.24"	72.28"	84.33"	96.38"
Depth	21.12"	21.12"	21.12"	21.12"
Weight	901 lbs.	1083 lbs.	1235 lbs.	1387 lbs.
Number of Wheels	15	18	21	24
Wheel Width	4.02"	4.02"	4.02"	4.02"
Wheel Diameter	16.3"	16.3"	16.3"	16.3"
Wheel Material	Notched Ductile Iron	Notched Ductile Iron	Notched Ductile Iron	Notched Ductile Iron
Axel	2"	2"	2"	2"
Bearings	Greasable	Greasable	Greasable	Greasable
Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch

Available Colors:





BALE UNROLLER



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



FEATURES & BENEFITS

- Category 1 and 2 Quick Hitch compatible
- 2 1/2" x 8" ASAE hydraulic cylinder
- 4" x 4" x 5/16" square tube frame
- Triple lug hitch
- Handles 4', 5' and 6' bales with ease

SPECIFICATIONS / OPTIONS

Models	BU Series
Overall Height	25 9/16"
Overall Width	69 1/2"
Overall Depth	66"
Weight	326 lbs
Max Spear Capacity	2,000 lbs.
Hitch	Cat. 1 & 2 Quick Hitch

Available Colors:





100 SERIES DISC HARROW



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



TRACTOR

FEATURES & BENEFITS

- Blade spacing: 7-1/2", 9" or combination
- Blade type: notched
- Frame tube: 2" square
- Bearing hanger: 3/8" plate, with 2 each 1/2" u-bolt
- Bearing type: sealed, self aligning , ball bearing
- Gang tube: 1-1/2" x 3" x 3/16"

SPECIFICATIONS / OPTIONS

Models	100-1	100-2	100-3	100-4	100-5	100-6	100-7	100-8	100-9	100-10	100-12	100-12
Number of Discs	12	12	16	16	14	14	18	18	12	12	16	16
Disc Size	16"	18"	16"	18"	16"	18"	16"	18"	16"	18"	16"	18"
Disc Type Front/Rear	Notched	Notched	Notched	Notched	Notched	Notched	Notched	Notched	Notched	Notched	Notched	Notched
Spacing Front	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"	9"	9"	9"	9"
Spacing Rear	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"
Overall Width	45 3/4"-48"	45 3/4"-48"	61"-68"	61"-68"	61"-68"	61"-68"	76 1/2"-83"	76 1/2"-83"	51"-58"	51"-58"	69"-76"	69"-76"
Weight	425 lbs	460 lbs	483 lbs	530 lbs	447 lbs	474 lbs	530 lbs	543 lbs	443 lbs	479 lbs	507 lbs	533 lbs

Available Colors:





DIRT DOG

200 SERIES DISC HARROW



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



FEATURES & BENEFITS

- 7 1/2" or 9" disc spacing available
- 2 1/2" square tube frame
- 3/8" gang hanger secured with two 5/8" u-bolts
- Sealed, self aligning ball bearings
- 65 horse power range
- 3" x 2" gang tubes

SPECIFICATIONS / OPTIONS

Models	200-1	200-2	200-3	200-4	200-5	200-6	200-7	200-8	200-9	200-10	200-12	200-12
Number of Discs	16	16	16	16	16	16	16	16	20	20	20	20
Disc Size	18"	20"	18"	20"	18"	20"	18"	20"	18"	20"	18"	20"
Disc Type Front/Rear	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain
Spacing Front	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"	7 1/2"	7 1/2"	7 1/2"	7- 1/2"
Spacing Rear	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"
Overall Width	63"	63"	63"	63"	73"	73"	73"	73"	78"	78"	78"	78"
Weight	646 lbs	701 lbs	645 lbs	700 lbs	675 lbs	727 lbs	675 lbs	727 lbs	700 lbs	770 lbs	700 lbs	770 lbs

Models	200-13	200-14	200-15	200-16	200-17	200-18	200-19	200-20	200-21	200-22	200-23	200-24
Number of Discs	18	18	18	18	20	20	20	20	22	22	22	22
Disc Size	18"	20"	18"	20"	18"	20"	18"	20"	18"	20"	18"	20"
Disc Type Front/Rear	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain
Spacing Front	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"
Spacing Rear	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"	7 1/2"	7 1/2"	7 1/2"	7 1/2"
Overall Width	78"	78"	78"	78"	96"	96"	96"	96"	96"	96"	96"	96"
Weight	695 lbs	766 lbs	695 lbs	766 lbs	740 lbs	815 lbs	740 lbs	815 lbs	858 lbs	902 lbs	858 lbs	902 lbs

Available Colors:





300 SERIES DISC HARROW



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



TRACTOR

FEATURES & BENEFITS

- Blade spacing: 7-1/2" , 9" or combination
- Blade type: notched
- Triple strap hitch
- Frame tube: 3" square
- Bearing hanger: 1/2" plate, with 2 each 5/8" u-bolt
- Bearing type: sealed, self aligning , ball bearing

SPECIFICATIONS / OPTIONS

Models	300-1	300-2	300-3	300-4	300-5	300-6	300-7	300-8	300-9	300-10	300-11	300-12	300-13	300-14
Number of Discs	20	20	20	20	18	18	18	18	20	20	20	20	24	24
Disc Size	20"	22"	20"	22"	20"	22"	20"	22"	20"	22"	20"	22"	20"	22"
Disc Type Front/Rear	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched
Spacing Front	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"	9"	9"	9"	9"	7 1/2"	7 1/2"
Spacing Rear	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7-1/2"	7-1/2"	9"	9"	9"	9"	7 1/2"	7 1/2"
Overall Width	78"	78"	78"	78"	78"	78"	78"	78"	96"	96"	96"	96"	96"	96"
Weight	1079 lbs	1198 lbs	1079 lbs	1198 lbs	1055 lbs	1172 lbs	1055 lbs	1172 lbs	1123 lbs	1246 lbs	1123 lbs	1246 lbs	1157 lbs	1282 lbs

Models	300-15	300-16	300-17	300-18	300-19	300-20	300-21	300-22	300-23	300-24	300-25	300-26	300-27	300-28
Number of Discs	24	24	22	22	22	22	24	24	24	24	26	26	26	26
Disc Size	20"	22"	20"	22"	20"	22"	20"	22"	20"	22"	20"	22"	20"	22"
Disc Type Front/Rear	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain	Notched /Plain	Notched /Plain	Notched	Notched	Notched /Plain
Spacing Front	7 1/2"	7 1/2"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"
Spacing Rear	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	7 1/2"	9"	9"	9"	9"	7 1/2"	7 1/2"	7 1/2"	7 1/2"
Overall Width	96"	96"	96"	96"	96"	96"	118"	118"	118"	118"	118"	118"	118"	118"
Weight	1157 lbs	1282 lbs	1144 lbs	1270 lbs	1144 lbs	1270 lbs	1217 lbs	1352 lbs	1217 lbs	1352 lbs	1326 lbs	1456 lbs	1326 lbs	1456 lbs

Available Colors:



PULL DISC HARROW



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



FEATURES & BENEFITS

- Triple lug tug
- 1" angle pin welded solid through main frame for added strength
- Single wheels standard optional dual wheels available
- Sealed, self aligning bearings
- Center sweep option available
- 4" x 3" frame construction

SPECIFICATIONS / OPTIONS

Models	DHP8	DHP10	DHP12
Drawbar Horsepower Requirement	35-100 hp	45-100 hp	55-100 hp
Approximate Transport Width	8'-10"	10'-10"	12'-4"
Max Cultivation Width	8'-6"	10'-6"	12'
Mainframe Width	60"	93 1/2"	93 1/2"
Approximate Weight Load on Each Blade	85-95	84-94	82-92
Disc Blade Sizes and Types	20-22" Notched or Smooth	20-22" Notched or Smooth	20-22" Notched or Smooth
Disc Blade Spacing	7 1/2" or 9"	7 1/2" or 9"	7 1/2" or 9"
Disc Bearing Type	Greaseable & Triple Sealed Ball Bearings	Greaseable & Triple Sealed Ball Bearings	Greaseable & Triple Sealed Ball Bearings
Number of Bearings	8	12	12
Forward Gang Angle Adjustment	15, 16.5, 18, 19.5, 21	15, 16.5, 18, 19.5, 21	15, 16.5, 18, 19.5, 21
Rear Gang Angle Adjustment	12, 13.5, 15, 16.5, 18	12, 13.5, 15, 16.5, 18	12, 13.5, 15, 16.5, 18
Hitch	Pull-type w/ clevis & hole for 1 1/4" pin	Pull-type w/ clevis & hole for 1 1/4" pin	Pull-type w/ clevis & hole for 1 1/4" pin

Available Colors:






ALL PURPOSE PLOW



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



TRACTOR

FEATURES & BENEFITS

- 2 1/2" x 2 1/2" x 3/8" angle steel frame
- Easily adjustability - 1" CNC hole spacing
- Economy priced
- Spring loaded auto reset shanks
- Replacable spring bolts
- Replaceable and reversible heat treated plow points

SPECIFICATIONS / OPTIONS

Models	APP48-3	APP60-5	APP66-5	SAPP66-7	APP85-7	APP85-9
Working Width	44"	56"	62"	62"	80"	80"
Overall Width	49 5/8"	61 5/8"	67 5/8"	67 5/8"	85 5/8"	85 5/8"
Overall Depth	39 3/4"	39 3/4"	39 3/4"	39 3/4"	39 3/4"	39 3/4"
Overall Height	40 3/8"	40 3/8"	40 3/8"	40 3/8"	40 3/8"	40 3/8"
Weight	206 lbs	228 lbs	284 lbs	367 lbs	386 lbs	455 lbs
Number of Shanks	3	5	5	7	7	9
Hole Spacing	1"	1"	1"	1"	1"	1"
Tooth	5/16"x2"x10 1/8" Rev 1080 High Carbon 38-44 Rockwell C	5/16"x2"x10 1/8" Rev 1080 High Carbon 38-44 Rockwell C	5/16"x2"x10 1/8" Rev 1080 High Carbon 38-44 Rockwell C	5/16"x2"x10 1/8" Rev 1080 High Carbon 38-44 Rockwell C	5/16"x2"x10 1/8" Rev 1080 High Carbon 38-44 Rockwell C	5/16"x2"x10 1/8" Rev 1080 High Carbon 38-44 Rockwell C
Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch	Cat. 1 Quick Hitch
Minimum HP	24	35	35	49	49	50

Available Colors:





CULTIVATOR



Take a Picture of This QR Code With Your Smart Phone to See it in Action



FEATURES & BENEFITS

- 2 1/2" x 2 1/2" x 3/8" angle frame
 - 3" x 3" x 3/8" angle tine frame
 - Easily adjustable tine spacing – 2" CNC hole spacing
- Tine locks standard to keep C-tines straight
 - Replaceable and reversible heat treated plow points
 - Cole and Covington planters accepted

SPECIFICATIONS / OPTIONS

Models	1RVC
Width	58"
Length	40"
Tractor HP	25-45
Weight	171 lbs
Moldboard/ tine dimensions	1 1/4" x 8" reversible curved points
Hitch	Cat. 1 Quick Hitch





SUB SOILER



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



TRACTOR

FEATURES & BENEFITS

- Bolt on shank foot, hitch and top link
- 3/4" x 6" shank made from 1060 wear resistant steel
- Replaceable heat treated plow points
- Shear bolt protected
- 3/4" x 6" shank made from wear resistant 1060 steel

SPECIFICATIONS / OPTIONS

Models	Sub Soiler
Overall Width	32 3/8"
Overall Height	50"
Horsepower	25-45
Weight	113 lbs
Shank Size	3/4" x 6"
Number of Shanks	1
Cutting Point	1/2" x 2 1/2" x 12"
Max Cutting Depth	25 5/8"
Hitch	Cat. 1 Quick Hitch

Available Colors:



HEAVY DUTY SUBSOILER



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



FEATURES & BENEFITS

- Category 1 and 2 Quick Hitch compatible
- Replacable heat treated plow points
- 1 1/4" Shanks
- Triple lug hitch
- Adjustable shank spacing on double shank models
- Parabolic shank for easy penetration
- 4" x 4" x 1/4" Main Tube

SPECIFICATIONS / OPTIONS


Models	SSHD1L	SSHD2L
Overall Width	41"	49"
Overall Height	43 1/2"	43 1/2"
Horsepower	Approximately 35 HP per shank up to 85 HP	Approximately 35 HP per shank up to 85 HP
Weight	276 lbs	450 lbs
Shank Size	1 1/4" x 9 7/16" 26 1/8"	1 1/4" x 9 7/16" 26 1/8"
Number of Shanks	1	2
Cutting Point	1" x 2 1/2" x 9 3/8"	1" x 2 1/2" x 9 3/8"
Max Cutting Depth	23 1/8"	23 1/8"
Hitch Category	Cat. 1 & 2 Quick Hitch	Cat. 1 & 2 Quick Hitch



LAYOFF PLOW



Take a Picture of This QR Code With
Your Smart Phone to See it in Action



TRACTOR

FEATURES & BENEFITS

- 3/4" x 4" shank
- Perfect for creating planting beds
- Replaceable heat treated 16" double wing cutting blade
- Category 1 and 2 Quick Hitch compatible

SPECIFICATIONS / OPTIONS

Models	LP
Overall Height	38"
Overall Width	32 3/8"
Horsepower	25-45
Weight	75 lbs
Number of Shanks	1
Shank Size	3/4" x 4
Cutting Point	16" x 4 3/4mm
Hitch	

Available Colors:

